Lifting Solutions Group
Axel Johnson International

# Swivel Eye / Jaw Crosby S4

## Product information



**Design:** Swivel with eye and jaw equipped with tapered roller thrust bearing.

**Features:**

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided.
- All jaws complete with bolts, nuts and cotter pins.
- Other types and capacities up to 1250 t available on demand.

... *Read more*

**Marking:** CE-mark
**Note:** Always check before use if your steel wire rope is suitable for use with a swivel.
**Warning:** Not to be used on demolition- (wrecking-) balls!

**Safety factor:** 5:1


**Traction Levage**
marketingtl@traclev.com

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Swivel Eye / Jaw Crosby S4

## Blueprint




## Technical data

| Part code | Rope Ø range mm | WLL ton | Swivel No | C mm | G mm | H mm | J mm | K mm | N mm | O mm | Q mm | R mm | S mm | T mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 422500300110 | 13 | 3 | 3-S-4 | 237 | 70 | 19.1 | 22.4 | 41.1 | 33.3 | 25.4 | 19.1 | 26.2 | 28.4 | 31.8 | 4.08 |
| 422500500110 | 16 | 5 | 5-S-4 | 256 | 76 | 22.4 | 25.4 | 57 | 41.1 | 28.4 | 25.4 | 32.5 | 31.8 | 31.8 | 5.6 |
| 422500850110 | 19 | 8.5 | 8-S-4 | 311 | 102 | 25.4 | 39.5 | 71.5 | 54 | 35.1 | 31.8 | 35.8 | 41.1 | 38.1 | 13.2 |
| 422501000110 | 22 | 10 | 10-S-4 | 409 | 114 | 38.1 | 44.5 | 86 | 89 | 44.5 | 42.9 | 42.9 | 70 | 47.8 | 20 |
| 422501500110 | 26 | 15 | 15-S-4 | 425 | 127 | 38.1 | 44.5 | 86 | 89 | 44.5 | 49.3 | 51.5 | 70 | 54 | 27.7 |
| 422502500110 |  | 25 | 25-S-4 | 546 | 152 | 51 | 51 | 117 | 93.5 | 60.5 | 57 | 58.5 | 98.5 | 60.5 | 61 |
| 422504500110 |  | 45 | 45-S-4 | 657 | 178 | 57 | 63.5 | 127 | 102 | 76 | 63.5 | 64.5 | 102 | 76 | 102 |


© November 2026 - All Rights Reserved