

Screw Pin Chain Shackle Crosby G-210

Product information

Design: Screw pin anchor shackles meet the performance requirements of Federal Specification RR-C-271G Type IVA, Grade A, Class 2, except for those provisions required of the contractor.

Material: Forged - Quenched and Tempered, with alloy pins.

Marking: According to standard, CE-marked

Temperature range: -40° C to 204° C

Finish: Hot Dip galvanized or self colored.

Standard: EN 13889, US. FED. SPEC. RR-C-271F

Safety factor: 6:1

Grade: 6



Part Code	WLL ton	Size inch	Weight kg	Delivery time
420100050030	0.5	1/4	0.05	-
420100750030	0.75	5/16	0.08	-
420100100030	1	3/8	0.13	-
420100150030	1.5	7/16	0.2	-
420100200030	2	1/2	0.27	-
420100330030	3.25	5/8	0.57	2
420100480030	4.75	3/4	1.19	-
420100650030	6.5	7/8	1.43	-
420100850030	8.5	1	2.15	-
420100950030	9.5	11/8	3.06	2
420101200030	12	11/4	4.11	-
420101350030	13.5	13/8	5.28	-
420101700030	17	11/2	7.23	-
420102500030	25	13/4	12.13	-
420103500030	35	2	19.19	-
420105500030	55	21/2	32.55	-

Blueprint

