



Eye Hook Crosby S-1316, Type SHUR-LOC

Product information

- 25% stronger than Grade 80
- Individually Proof tested to 2-1/2 times the Working Load Limit with certification.
- Recessed trigger design is flush with the hook body, protecting the trigger from potential damage.
- Easy to operate with enlarged thumb access.
- Positive Lock Latch is Self-Locking when hook is loaded.
- Eye style is designed with "Engineered Flat" to connect to S-1325 chain coupler.
- Suitable for use with Grade 100 and Grade 80 chain.
- The SHUR-LOCK hook, if properly installed and locked, can be used for personnel lifting applications and meets the intent of OSHA Rule 1926. 1431 (g)(1)(i)(A) and 1926. 1501(g)(4)(iv)(B).
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.

Material: Forged Alloy steel - Quenched and Tempered.

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 10

Part Code	WLL ton	Chain mm	A mm	C mm	D mm	E mm	F mm	H mm	J mm	L mm	AA mm	Weight kg	Delivery time
154061	1.45	6	19.8	100	20.1	66	17	7.87	16	29.5	38.1	0.39	2
154062	2.6	7-8	27.4	135	27.9	88.9	22.1	9.91	20.6	37.6	51	0.82	2
154063	4	10	33	167	29.7	112	27.9	12.9	23.9	46.5	63.5	1.54	2
154064	6.8	13	41.9	209	42.4	139	32	17	29.5	56.4	76.2	2.72	2
154065	10.3	16	55.9	256	51.8	167	38.1	22.1	38.1	67.3	89	6.85	2
154066	16	18-20	64	274	56.4	197	51.1	22.1	51.6	89.4	-	8.62	2
154067	20	22	72.9	317	62.2	222	57.7	24.9	55.9	97.3	-	12.7	2
154068	27.1	26	80	371	81.5	251	62.5	32	68.1	104	-	22.5	2

Blueprint

