

Welded Master Link Assembly Crosby A-1346

Product information



Features:

- Ratings below are for use with chain slings fabricated in accordance with ASTM B30.9.
- Individually Proof Tested to values shown.
- Meets or exceed all requirements of ASME B30.26 including identification, ductility, design factor, proof load and temperature requirements. Importantly, this master link meet other critical performance requirements including fatigue life, impact properties and material traceability, not addressed by ASME B30.26 ... [Read more](#)

Material: Alloy Steel - Quenched and Tempered.

Marking: According to standard, Code and grade

Finish: Painted


Standard: EN 1677-4

Safety factor: 5:1

Grade: 10

Welded Master Link Assembly Crosby A-1346

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	Weight kg
402100320060	6	3.2	13	60	120	13	60	120	1.1
402100410060	6	4.1	17	90	160	13	60	120	1.6
402100430060	7	4.2	19	90	160	13	60	120	1.8
402100700060	8	7	22	100	180	17	90	160	3.3
402100700061	8	7	22	145	275	17	90	160	4.1
402100850060	10	8.5	22	100	180	19	90	160	3.8
402100890061	10	8.9	25	115	210	19	90	160	4.6
402100890060	10	8.9	25	145	275	19	90	160	5.2
402101450060	13	14.5	28	145	275	22	100	180	7.1
402101700060	13	17	32	145	275	25	115	210	9.6
402102360060	16	23.6	36	155	285	28	110	190	12.7
402102810060	16	28.1	40	140	270	32	145	275	18.4
402103830060	19-20	38.3	45	180	340	36	155	285	26.6
402104500061	22-23	45	51	215	390	40	140	270	35.5
402106700061	26	67	55	203	406	51	215	390	61.1