



Welded Master Link Crosby A-347

Product information

Master link with large inner diameter and length.

These rings with auxiliaries have the dimensions that allow the manufacture of steel wire ropes slings with 3 or 4 legs.

Material: Alloy steel — Quenched & Tempered

Marking: According to standard, Manufacturers name, traceability code.

Standard: EN 1677-4

Safety factor: 5:1

Grade: 8

Part code	Chain diameter mm	WLL ton	Chain G80 3 and 4 legs	Chain Ø inch	Chain G100 3 and 4 legs	A	B mm	C mm	D mm	E mm	F mm	G mm	Weight kg
401100320150	13	3.2	6	-	6	13	60	120	13	120	60	6.5	1.1
401100410150	13-17	4.1	6-7	11/16	6	17	90	160	13	120	60	6.5	1.6
401100420150	13-19	4.2	7	3/4	6-7	19	90	160	13	120	60	6.5	1.8
401100700150	17-22	7	10	-	8	22	100	180	17	160	90	8.5	3.3
401100700151	17-22	7	10	-	8	22	145	275	17	160	90	8.5	4.1
401100850151	19-22	8.5	10	-	10	22	100	180	19	160	90	8.5	3.8
401100890151	19-25	8.9	10	-	10	25	115	210	19	160	90	8.5	4.6
401100890150	19-25	8.9	10	1	10	25	145	275	19	160	90	8.5	5.3
401101450150	22-28	14.5	13	1-1/8	13	28	145	275	22	180	100	10.5	7.2
401101700150	25-31	17	16	1-7/32	13	32	145	275	25	210	115	13.5	9.9
401102360150	28-36	23.6	16	-	16	36	155	285	28	190	110	13.5	12.7
401102810152	32-40	28.1	19-20	-	16	40	140	270	32	275	145	16.7	18.4
401103830150	36-45	38.3	22	1-3/4	19-20	45	180	340	36	285	155	-	26.7
401106700151	51-55	67	32	-	26	55	203	406	51	390	215	-	61.1

Blueprint

