Lifting Solutions Group
Axel Johnson International

# Welded Master Link Crosby A-347

**Product information**

Master link with large inner diameter and length.
These rings with auxiliaries have the dimensions that allow the manufacture of steel wire ropes slings with 3 or 4 legs.

... *Read more*

**Material:** Alloy steel — Quenched & Tempered
**Marking:** According to standard, Manufacturers name, traceability code.
**Standard:** EN 1677-4

**Safety factor:** 5:1
**Grade:** 8

**Traction Levage**
marketingtl@traclev.com

© October 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Welded Master Link Crosby A-347

## Blueprint




## Technical data

| Part code | Chain diameter mm | WLL ton | Chain G80 3 and 4 legs | Chain Ø inch | Chain G100 3 and 4 legs | A mm | B mm | C mm | D mm | E mm | F mm | G mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 401100320150 | 13 | 3.2 | 6 | - | 6 | 13 | 60 | 120 | 13 | 120 | 60 | 6.5 | 1.1 |
| 401100410150 | 13-17 | 4.1 | 6-7 | 11/16 | 6 | 17 | 90 | 160 | 13 | 120 | 60 | 6.5 | 1.6 |
| 401100420150 | 13-19 | 4.2 | 7 | 3/4 | 6-7 | 19 | 90 | 160 | 13 | 120 | 60 | 6.5 | 1.8 |
| 401100700150 | 17-22 | 7 | 10 | - | 8 | 22 | 100 | 180 | 17 | 160 | 90 | 8.5 | 3.3 |
| 401100700151 | 17-22 | 7 | 10 | - | 8 | 22 | 145 | 275 | 17 | 160 | 90 | 8.5 | 4.1 |
| 401100850151 | 19-22 | 8.5 | 10 | - | 10 | 22 | 100 | 180 | 19 | 160 | 90 | 8.5 | 3.8 |
| 401100890151 | 19-25 | 8.9 | 10 | - | 10 | 25 | 115 | 210 | 19 | 160 | 90 | 8.5 | 4.6 |
| 401100890150 | 19-25 | 8.9 | 10 | 1 | 10 | 25 | 145 | 275 | 19 | 160 | 90 | 8.5 | 5.3 |
| 401101450150 | 22-28 | 14.5 | 13 | 1-1/8 | 13 | 28 | 145 | 275 | 22 | 180 | 100 | 10.5 | 7.2 |
| 401101700150 | 25-31 | 17 | 16 | 1-7/32 | 13 | 32 | 145 | 275 | 25 | 210 | 115 | 13.5 | 9.9 |
| 401102360150 | 28-36 | 23.6 | 16 | - | 16 | 36 | 155 | 285 | 28 | 190 | 110 | 13.5 | 12.7 |
| 401102810152 | 32-40 | 28.1 | 19-20 | - | 16 | 40 | 140 | 270 | 32 | 275 | 145 | 16.7 | 18.4 |
| 401103830150 | 36-45 | 38.3 | 22 | 1-3/4 | 19-20 | 45 | 180 | 340 | 36 | 285 | 155 | - | 26.7 |
| 401106700151 | 51-55 | 67 | 32 | - | 26 | 55 | 203 | 406 | 51 | 390 | 215 | - | 61.1 |


© October 2026 - All Rights Reserved