

Swivel Regular Crosby G-402

Product information



Design: Chain swivels with out bearing. According to Federal Specification RR-C-271F.

... [Read more](#)

Material: Hot dip Galvanized - Quenched & Tempered

Marking: WLL


Finish: Galvanized

Note: The swivels are positioning devices and are not intended to rotate under load. For load swivels, see ball bearing swivels.

Safety factor: 5:1

Swivel Regular Crosby G-402

Blueprint



Technical data

Part code	Diameter mm	WLL ton	A mm	B mm	C mm	D mm	J mm	M mm	R mm	S mm	Weight kg
422500060120	8	0.57	41.4	20.6	25.4	31.8	20.6	9.65	90.4	52.3	0.18
422500100120	10	1.02	51	23.9	31.8	38.1	25.4	12.7	109	63.5	0.32
422500160120	13	1.63	63.5	33.3	38.1	51	33.3	16	138	81	0.6
422500240120	16	2.36	76	39.5	44.5	60.5	38.1	19.1	167	98.5	1.13
422500330120	19	3.27	89	44.5	51	67	47.8	22.4	183	109	1.82
422500450120	22	4.54	102	52	57	77.5	54	25.4	213	127	2.83
422500570120	25	5.67	114	58.5	63.5	89	60.5	28.7	245	146	4.06
422500820120	32	8.16	143	68.5	79.5	93.5	76	38.1	291	172	7.42
422502050120	38	20.5	180	98.5	104	98.5	95.2	57	424	252	20.8