

H type weld-on pad eye



Product information

Welding must be carried out according to EN ISO 5817 resp. 15 429 by a qualified welder according to EN 287-1 standard.

All surfaces and supports must be clean.

Material: Steel

Marking: According to standard, CE-marked, WLL, supplier

Finish: Black

Standard: EN ISO 5817

Safety factor: 5:1

| Part code | Diameter mm | WLL ton | A mm | B mm | C mm | D mm | Weight kg/100pc |
|--------------|-------------|---------|------|------|------|------|-----------------|
| 421100020540 | 9 | 0.2 | 24 | 43 | 10 | 54 | 6 |
| 421100050540 | 12 | 0.5 | 31 | 55 | 12 | 68 | 14 |
| 421100100540 | 13 | 1 | 43 | 67 | 12 | 85 | 18 |
| 421100200540 | 18 | 2 | 48 | 82 | 16 | 105 | 40 |
| 421100300540 | 21 | 3 | 57 | 95 | 17 | 128 | 66 |
| 421100400540 | 25 | 4 | 67 | 107 | 15 | 148 | 102 |
| 421100600540 | 28 | 6 | 82 | 135 | 24 | 189 | 192 |
| 421100800540 | 30 | 8 | 100 | 165 | 35 | 210 | 312 |

Blueprint

