

## **Chain Sling CSX-276 Grade 10**

## **Product information**

**Design:** Chain sling with master link on one end and clevis safety hooks on the other ends. ø 19 and 22 mm chain are fitted with eye safety hooks. Other combinations possible on demand.

Dimensions: Ø 6-22 mm (other dimensions on demand).

Material: Alloy steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to 200°C (up to 380° possible on demand)

Standard: EN 818-4

Warning: Not to be heat-treated

Safety factor: 4:1 Grade: 10

Part code	WLL ton
2409	2
2409	2
2409	2
2409	2
2409	2
2409	2
2409	2

2409	2
2409	2
2409	2.65
2409	2.65
2409	2.65
2409	2.65
2409	2.65
2409	2.65
2409	2.65
2409	2.65
2409	2.65
2409	3.55
2409	3.55
2409	3.55
2409	3.55
2409	3.55
2409	3.55
2409	3.55
2409	3.55
2409	3.55
148961	5.6
2409	5.6
2409	5.6

2409	5.6
2409	5.6
2409	5.6
2409	5.6
2409	5.6
2409	5.6
148962	9.5
2409	9.5
2409	9.5
2409	9.5
2409	9.5
2409	9.5
2409	9.5
2409	9.5
2409	9.5
148963	14
2409	14
2409	14
2409	14
2409	14
2409	14
2409	14
2409	14

2409	14	
148964	20	
2409	20	
2409	20	
2409	20	
2409	20	
2409	20	
2409	20	
2409	20	
2409	20	
2409	26.5	
2409	26.5	
2409	26.5	
2409	26.5	
2409	26.5	
2409	26.5	
2409	26.5	
2409	26.5	
2409	26.5	