



## Connecting Link V/S Grade 10

### Product information

Connecting link for: masterlink - chain, chain - chain, (eye)hook - chain.

**Material:** Alloy steel.

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to 380°C

**Finish:** Violet powder coated.

**Standard:** EN 1677-1

(+ 25% WLL)

**Note:** Not to be heat-treated.

**Warning:** For straight in-line pull only. Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 10

| Part Code  | Code      | Chain diameter<br>mm | WLL<br>ton | For chain ø<br>mm | B<br>mm | C<br>mm | D<br>mm | E<br>mm | G<br>mm | S<br>mm | Weight<br>kg | Delivery time |
|------------|-----------|----------------------|------------|-------------------|---------|---------|---------|---------|---------|---------|--------------|---------------|
| 11.0665653 | V/S 6     | 6                    | 1.4        | 6                 | 39      | 8       | 8       | 44      | 14      | 11      | 0.11         | 15            |
| 11.0669997 | V/S 7     | 7                    | 1.9        | 7                 | 47      | 10      | 9       | 51      | 17      | 13      | 0.2          | 15            |
| 161123     | V/S 8     | 8                    | 2.5        | 8                 | 55      | 12      | 10      | 62      | 18      | 14      | 0.29         | 15            |
| 161124     | V/S 10    | 10                   | 4          | 10                | 64      | 15      | 13      | 72      | 24      | 18      | 0.52         | 15            |
| 161125     | V/S 13    | 13                   | 6.7        | 13                | 79      | 20      | 17      | 88      | 28      | 22      | 0.91         | 15            |
| 161126     | V/S 16    | 16                   | 10         | 16                | 106     | 21      | 21      | 103     | 33      | 29      | 1.34         | 15            |
| 161127     | V/S 19/20 | 19                   | 16         | 19-20             | 123     | 30      | 24      | 115     | 42      | 35      | 3.33         | 15            |
| 161128     | V/S 22    | 22                   | 19         | 22                | 148     | 34      | 25      | 161     | 51      | 39      | 3.14         | 15            |
| 11.0676492 | V/S 26    | 26                   | 26.5       | 26                | 175     | 40      | 30      | 190     | 60      | 46      | 5.72         | 15            |

Blueprint

