



## Master Link A/S Grade 10

### Product information

Designed for use in 1-leg and 2-leg slings.

**Material:** Alloy steel.

**Marking:** According to standard, CE-marked, code and grade.

**Finish:** Violet powder coated.

**Standard:** EN 1677-4

**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 10

| Part Code  | Code      | WLL<br>ton | Chain<br>mm | d<br>mm | t<br>mm | w<br>mm | s<br>mm | Weight<br>kg | Delivery time |
|------------|-----------|------------|-------------|---------|---------|---------|---------|--------------|---------------|
| 11.021262  | A/S-13-10 | 2.3        | 6/7         | 13      | 110     | 60      | 10      | 0.34         | 15            |
| 161106     | A/S-16-10 | 3.5        | 8           | 17      | 110     | 60      | 14      | 0.55         | 15            |
| 161110     | A/S-18-10 | 5          | 10          | 19      | 135     | 75      | 14      | 0.94         | 15            |
| 161111     | A/S-22-10 | 7.6        | 13          | 23      | 160     | 90      | 17      | 1.64         | 15            |
| 161112     | A/S-26-10 | 10         | 16          | 27      | 180     | 100     | 20      | 2.53         | 15            |
| 161113     | A/S-32-10 | 14         | 19          | 33      | 200     | 110     | 26      | 4.28         | 15            |
| 161114     | A/S-36-10 | 25.1       | 22          | 36      | 260     | 140     | -       | 6.22         | 15            |
| 11.0270046 | A/S-45-10 | 30.8       | 26          | 45      | 340     | 180     | -       | 12.74        | 15            |
| 11.0270050 | A/S-50-10 | 40         | 26          | 50      | 350     | 190     | -       | 16.55        | 15            |

## Blueprint

