



Eye Grip Safe Locking Hook X-950

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.
- Avoid finger injury by the grip design.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-3

Safety factor: 4:1

Grade: 10

Part Code	Chain diameter mm	WLL ton	A mm	D mm	H mm	K mm	O mm	P mm	T mm	W mm	Weight kg	Delivery time
11.16X-950-10	10	4	33	13	31	176	49	71	27	137	1.9	15
11.16X-950-13	13	6.7	40	16	39	226	64	80	34	174	4	15
11.16X-950-16	16	10	50	21	47	277	78	114	39	212	6.3	15
11.16X-950-20	20	16	62	23	55	329	92	127	54	251	12.3	15
11.16X-950-22	22	19	70	24	59	350	98	151	56	258	14	15

Blueprint

