

## WINPRO flex 300 Chain PC/B cutting length

### Product information



**General:** Specially rugged profile chain in grade 12 for lifting.

**Standard:** Corresponding to PAS 1061 with modifications.

**Material:** Alloy steel grade 12.

**Marking:** Every link is marked with manufacturer ID and grade.

**Temperature range:** -60°C to +300°C.

**Finish:** Light blue powdercoated.

**Warning:** Not to be heat-treated.

**Grade:** 12

| Part Code  | Chain diameter<br>mm | WLL<br>ton | Min. Breaking force<br>kN. | D<br>mm | E<br>mm | H<br>mm | Weight<br>kg/m | Delivery time |
|------------|----------------------|------------|----------------------------|---------|---------|---------|----------------|---------------|
| 153598     | 7                    | 2.36       | -                          | 7       | 22      | 10      | 1.36           | 15            |
| 153590     | 8                    | 3          | 118                        | 8       | 25      | 11      | 1.64           | 15            |
| 152091     | 10                   | 5          | 196                        | 10      | 33      | 14      | 2.7            | 15            |
| 153071     | 13                   | 8          | 314                        | 13      | 41      | 19      | 4.8            | 15            |
| 11.6677083 | 16                   | 12.5       | 491                        | 16      | 51      | 23      | 7.17           | 15            |

Blueprint

