Lifting Solutions Group
Axel Johnson International

Clevis Masterlink X-059

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL
... Read more

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.
Temperature range: -40° up to +200°C (without reduction in WLL).
Finish: Blue painted.
Standard: EN 1677-4


Safety factor: 4:1
Grade: 10

Traction Levage
marketingtl@traclev.com
© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Clevis Masterlink X-059

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	A mm	G mm	H mm	K mm	L mm	T mm	Weight kg
402100250510	7-8	2.5	10	65	15	103	83	19	0.4
402100400510	10	4	11	96	19	133	108	19	0.8
402100670510	13	6.7	14	108	22	168	136	25	1.5
402101000510	16	10	18	124	26	203	165	27	2.4

© November 2026 - All Rights Reserved