Lifting Solutions Group
Axel Johnson International

# GN H14 Forged Rope Shackle Sling Protector- Wide Body

**Product information**

We deliver a quality GN H14 Forged Rope Shackle Sling Protector- Wide Body and alloy steel quenched and tempered shackle.

... *Read more*




**Material:** Alloy steel quenched and tempered.
**Marking:** According to standard
**Temperature range:** -20°C up to 200°C (WLL 40 ton) -40°C up to 200°C (above WLL 40 ton)
**Finish:** Painted.
**Standard:** EN 10204
**Note:** WLL 2500 ton up to 3000 ton have SF 4,5:1. WLL 3500 ton up to 4000 have SF 4:1.


**Safety factor:** 5:1

**Traction Levage**
marketingtl@traclev.com
© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# GN H14 Forged Rope Shackle Sling Protector- Wide Body

## Blueprint




## Technical data

| Part code | WLL ton | A mm | B mm | C mm | D mm | E mm | F mm | G mm | L mm | R mm | X mm | Y mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 420104000330 | 40 | 45 | 51 | 84 | 200 | 109 | 140 | 97 | 252 | 53 | 232 | 331 | 14 |
| 420105500330 | 55 | 65 | 56 | 95 | 250 | 130 | 160 | 110 | 300 | 55 | 288 | 400 | 33 |
| 420107500330 | 75 | 75 | 70 | 110 | 300 | 150 | 185 | 120 | 345 | 60 | 334 | 485 | 53 |
| 420112500330 | 125 | 85 | 80 | 140 | 370 | 165 | 220 | 150 | 395 | 80 | 390 | 583 | 85 |
| 420115000330 | 150 | 90 | 95 | 150 | 400 | 200 | 250 | 170 | 420 | 90 | 429 | 638 | 115 |
| 420120000330 | 200 | 105 | 105 | 160 | 480 | 225 | 275 | 205 | 470 | 110 | 484 | 755 | 183 |
| 420125000330 | 250 | 120 | 120 | 180 | 550 | 240 | 300 | 230 | 520 | 125 | 540 | 850 | 255 |
| 420130000330 | 300 | 140 | 134 | 195 | 600 | 280 | 350 | 265 | 580 | 140 | 628 | 947 | 368 |
| 420140000330 | 400 | 160 | 160 | 230 | 620 | 330 | 370 | 320 | 655 | 170 | 689 | 1,035 | 571 |
| 420150000330 | 500 | 170 | 180 | 265 | 680 | 350 | 440 | 340 | 710 | 180 | 779 | 1,125 | 719 |
| 420160000330 | 600 | 180 | 200 | 290 | 720 | 405 | 490 | 370 | 795 | 190 | 847 | 1,213 | 960 |
| 420170000330 | 700 | 210 | 215 | 320 | 780 | 465 | 540 | 400 | 880 | 210 | 957 | 1,330 | 1,350 |
| 420180000330 | 800 | 220 | 230 | 345 | 800 | 465 | 555 | 420 | 925 | 220 | 990 | 1,358 | 1,400 |
| 420190000330 | 900 | 235 | 250 | 370 | 850 | 480 | 585 | 440 | 1,010 | 235 | 1,060 | 1,450 | 1,850 |
| 420110000331 | 1,000 | 235 | 270 | 400 | 850 | 530 | 615 | 460 | 1,050 | 240 | 1,091 | 1,490 | 2,050 |
| 420112500331 | 1,250 | 275 | 300 | 455 | 960 | 570 | 645 | 560 | 1,210 | 285 | 1,205 | 1,695 | 3,000 |
| 420115500331 | 1,550 | 275 | 320 | 485 | 980 | 610 | 680 | 580 | 1,240 | 290 | 1,240 | 1,745 | 3,300 |
| 420117500331 | 1,750 | 310 | 360 | 500 | 1,120 | 660 | 700 | 600 | 1,325 | 300 | 1,346 | 1,960 | 4,700 |
| 420120000331 | 2,000 | 320 | 385 | 520 | 1,140 | 680 | 705 | 620 | 1,365 | 310 | 1,368 | 2,012 | 4,800 |


© November 2026 - All Rights Reserved