



## Clevis Self Locking Hook X-026

### Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Manufactured in accordance with EN 1677-3 and ASME B30.26.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C.
- Magnaflux crack detection is performed 100% on each batch.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

**Material:** Quenched and tempered alloy steel.

**Marking:** According to standard, Size, grade, manufacturer ID, traceability.

**Temperature range:** -40°C up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-3

**Safety factor:** 4:1

**Grade:** 10

| Part Code     | Chain diameter<br>mm | WLL<br>ton | A<br>mm | H<br>mm | K<br>mm | P<br>mm | T<br>mm | Weight<br>kg | Delivery time |
|---------------|----------------------|------------|---------|---------|---------|---------|---------|--------------|---------------|
| 11.16X-026-06 | 6                    | 1.4        | 7       | 19      | 94      | 28      | 15      | 0.4          | 15            |
| 173707        | 7-8                  | 2.5        | 9       | 24      | 119     | 34      | 20      | 0.9          | 15            |
| 169646        | 10                   | 4          | 11      | 30      | 142     | 44      | 26      | 1.4          | 2             |
| 169583        | 13                   | 6.7        | 15      | 39      | 178     | 52      | 30      | 3            | 15            |
| 148921        | 16                   | 10         | 18      | 49      | 213     | 60      | 36      | 5            | 2             |
| 148922        | 20                   | 16         | 25      | 65      | 251     | 70      | 53      | 11           | 15            |
| 11.16X-026-22 | 22                   | 19         | 24      | 63      | 273     | 80      | 49      | 13.5         | 15            |

Blueprint

