

## Eye Self Locking Hook X-025

---

### Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C.
- Magnaflux crack detection is performed 100% on each batch.

When fitting G10 components are added to G8 chain, the sling is rated at GR WLL I  
... [Read more](#)

---

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, Size, grade, manufacturer ID, traceability.

**Temperature range:** -40°C up to +200°C (without reduction in WLL).

**Finish:** Blue painted.


**Standard:** EN 1677-3

**Safety factor:** 4:1

**Grade:** 10

## Eye Self Locking Hook X-025

### Blueprint



### Technical data

Part code	Chain diameter mm	WLL ton	A mm	D mm	H mm	K mm	P mm	T mm	Weight kg
402300140720	6	1.4	21	10	19	110	28	15	0.5
402300250720	7-8	2.5	25	11	24	136	34	20	0.8
402300400720	10	4	32	13	30	167	44	26	1.5
402300670720	13	6.7	40	16	39	207	51	30	3
402301000720	16	10	50	21	49	252	60	36	5.8
402301600720	20	16	60	23	65	290	70	53	10
402301900720	22	19	70	24	63	319	80	49	12.5
402302650720	26	26.5	80	25	69	343	99	56	15