



Swivel Self Locking Hook X-027

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Proof load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-3

Warning: This hook is a positioning device and is not intended to rotate under load.

Safety factor: 4:1

Grade: 10

Part Code	Chain diameter mm	WLL ton	A mm	B mm	D mm	H mm	K mm	P mm	T mm	Weight kg	Delivery time
11.16X-027-06	6	1.4	32	25	12	19	149	28	15	0.7	15
11.16X-027-07	7-8	2.5	36	30	13	24	186	34	20	1.2	15
11.16X-027-10	10	4	41	38	16	30	218	44	26	2	15
11.16X-027-13	13	6.7	46	48	21	39	276	51	30	4.1	15
11.16X-027-16	16	10	61	56	23	49	329	60	36	7.2	15
174150	20	16	74	86	25	65	403	70	53	13	15
11.16X-027-22	22	19	97	98	33	63	455	80	49	20	15
11.16X-027-26	26	26.5	123	120	51	69	535	99	56	33	15

Blueprint

