



Snatch Block S - Schackle |Discontinued

Product information

General: Intended for general lifting purposes. Can also be used for pulling. WLL in table applies for load on head fitting/shackle.

Features:

- Snatch block type with covering side plates.
- Provided with swiveling bow shackle.
- Grease fitting in the shaft and cross head.
- Bronze bushed sheave in 2-4 tons blocks and roller bearings in larger sizes.

Material: Steel.

Marking: Type, WLL and wire rope diameter.

Finish: Blue painted.

Part Code	WLL ton	Diameter mm	TA mm	TB mm	TC mm	Ø D1 mm	Ø D2 mm	Weight kg	Delivery time
16.15121030215	2	7-9	82	70	290	75	58	4	15
16.15121040415	4	10-12	120	70	358	115	90	6	15
16.15121060415	4	16-19	160	70	432	150	120	14	15
16.15121060815	8	19-22	160	93	497	150	120	15	15
16.15121080815	8	19-22	210	93	550	200	165	16	15
16.15121101015	10	24-26	260	115	681	250	205	38	15
16.15121101215	12	24-26	260	115	683	250	205	42	15
16.15121121215	12	24-26	310	133	767	300	250	56	15
16.15121181515	15	22-24	210	102	663	200	165	24	15
16.15121121515	15	24-26	310	133	788	300	250	65	15
16.15121142215	22	28-32	365	140	962	355	305	90	15
16.15121162215	22	28-32	415	140	1,019	405	350	108	15
16.15121182215	22	28-32	465	180	1,069	450	395	120	15
16.15121123015	30	28-30	310	193	1,023	300	245	125	15
16.15121163015	30	32-35	415	155	1,121	405	350	135	15
16.15121203015	30	32-35	514	162	1,256	508	440	210	15
16.15121143515	35	32-35	365	193	1,058	350	280	130	15
16.15121245015	50	46-50	625	275	1,525	600	500	418	15

Blueprint

