

Tendeur à deux chapes DIN 1480



Informations du produit

Tendeur pour tendre des câbles.

Matériau: Acier Fe-430 b

Marquage: Selon la norme, Marqué CE

Norme: DIN 1480

Attention: Ne pas utiliser pour du levage

Réf.	Longueur mm	Filetage	Amm mm	Bmm mm	Cmm mm	Dmm mm	Emm mm	Fmm mm	Gmm mm	Hmm mm	L1mm mm	L2mm mm	Poids (kg)
492126000550	174-260	M6	12	110	55	7	19	19	12	87	174	260	0,09
492127000550	190-270	M8	15	110	55	9	23	25	14	95	190	270	0,22
492131200550	222-312	M10	18	125	68	11	26	25	17	111	222	312	0,33
492131000550	235-310	M12	21	125	69	15	32	37	24	122	235	310	0,58
492139500550	310-395	M14	22	140	91	19	37	43	30	155	310	395	1,04
492143500550	332-435	M16	27	170	91	25	41	48	32	166	332	435	1,21
492146000550	337-460	M18	27	180	91	25	50	48	38	170	337	460	2,02
492151000550	378-510	M20	34	200	120	25	50	48	40	200	378	510	2,14
492158500550	445-585	M22	36	220	120	30	61	55	45	230	445	585	3,37
492167200550	494-672	M24	39	255	130	31	65	66	52	247	494	672	3,77
492161700550	452-617	M27	45	255	130	28	72	62	48	226	452	617	6,12
492167900550	514-679	M30	45	255	130	38	92	79	56	257	514	679	7,54
492175500550	556-755	M33	48	295	150	38	92	85	60	278	556	755	8,94
492183000550	640-830	M36	55	295	170	60	97	94	76	297	640	830	12,98
492180800550	594-808	M39	58	330	170	45	85	86	76	297	594	808	16,01

Dimensions

